

POWER ADDITIVE



OCTANE BOOSTER

Klotz Octane Booster is a concentrated tetraethyl lead substitute formulated to increase the octane rating of gasoline up to 10 numbers or more. Helps eliminate engine damaging detonation, spark knock, pre-ignition, and pinging from low octane gasoline. Octane Booster modifies the burn speed and flash point of gasoline to create a stable combustion chamber flame front, maximizing performance and power. Stabilizes oxygenated gasoline to prevent lean-out conditions. Klotz Octane Booster provides needed upper cylinder lubrication that is missing in unleaded gasoline.

- Raise octane rating up to 10 numbers
- Improves throttle response and acceleration
- Prevents pinging and spark knock
- Stabilizes oxygenated gasoline
- Absorbs moisture in fuel system
- Preserves gasoline up to 16 months
- Eliminates gum and varnish build-up
- Catalytic converter safe

► APPLICATION:

2/4-stroke gasoline - all

► CHARACTERISTICS:

Color: Green
Specific Gravity: .800 @ 60°F



► DIRECTIONS:

Compatibility: All gasoline, synthetic lubricants and petroleum oils. Will blend lubricants and oils with gasoline in extreme temperatures.

Octane Booster: 1oz Octane Booster per gallon of gasoline will raise the octane by 2 1/2 numbers. For best performance match the octane to the engines compression ratio. Use octane index A.K.I. and R+M/2. Octane Booster is effective in inverse ratios to the octane level of the base gasoline. All gasoline varies in sensitivity and quality.

Gasoline Stabilizer: Preserves gasoline during storage. Add 1oz Octane Booster per gallon of gasoline for 6 to 8 months, or 2 oz per gallon of gasoline for 12 to 16 months.

Fuel System Cleaner: Add 16 oz Octane Booster to gas tank, treats up to 20 gallons of gasoline. Protect painted surfaces, wash off immediately with water to prevent damage. Will not harm catalytic converters.

► **AVAILABILITY:** KL-602 16 oz; KL-628 gallon; 30 & 55 gallon drum